

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2015/830



Article No.: 34501001
Print date: 10.12.2018
Version: 2.1

Empire Dirt Blocker
Revision date: 11.06.2018
Issue date: 24.04.2018

EN
Page 1 / 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Identification of the substance or mixture
Empire Dirt Blocker
For Sneakers & Caps
100% Rain & Stain Repellent

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

impregnation spray for leather and textiles

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

Nanogate Textile & Care Systems GmbH
Zum Schacht 3
D-66287 Göttelborn

Telephone: +49 - (0)6825 / 9591 - 0
Telefax: +49 - (0)6825 / 9591 - 852
E-mail info@nanogate.com

Dept. responsible for information:

E-mail (competent person) msds@nanogate.com

1.4. Emergency telephone number

111 (England, Wales, Scotland)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Aerosol 1 / H222	Aerosol	Extremely flammable aerosol.
Aerosol 1 / H229	Aerosol	Pressurised container: May burst if heated.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Danger

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe aerosol.
P271	Use only outdoors or in a well-ventilated area.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Article No.: 34501001
Print date: 10.12.2018
Version: 2.1

Empire Dirt Blocker
Revision date: 11.06.2018
Issue date: 24.04.2018

EN
Page 2 / 8

contains:

propane-2-ol

Supplemental Hazard information (EU)

EUH208 Contains zirconium tetrabutanolate. May produce an allergic reaction.

2.3. **Other hazards**

Caution/Important note: Inhalation may be damaging to health. Use only outdoors or in a well ventilated area. Spray for just a few seconds. Spray larger leather products or textiles outdoors only and allow to air-dry thoroughly. Keep away from children!

SECTION 3: Composition / information on ingredients

3.2. **Mixtures**

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Chemical name classification: // Remark	Wt %
200-661-7 67-63-0 603-117-00-0	01-2119457558-25 propane-2-ol Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	50 < 70
203-448-7 106-97-8 601-004-00-0	01-2119474691-32 butane compressed gas H280 / Flam. Gas 1 H220	20 < 25
204-658-1 123-86-4 607-025-00-1	01-2119485493-29 n-butyl acetate Flam. Liq. 3 H226 / STOT SE 3 H336	12,5 < 15
200-827-9 74-98-6 601-003-00-5	01-2119486944-21 propane compressed gas H280 / Flam. Gas 1 H220	5 < 7
200-857-2 75-28-5 601-004-00-0	01-2119485395-27 isobutane compressed gas H280 / Flam. Gas 1 H220	1 < 3
213-995-3 1071-76-7	zirconium tetrabutanolate Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Flam. Liq. 3 H226	0,1 < 0,15

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. **Description of first aid measures**

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. **Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

Article No.: 34501001
Print date: 10.12.2018
Version: 2.1

Empire Dirt Blocker
Revision date: 11.06.2018
Issue date: 24.04.2018

EN
Page 3 / 8

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways. Cool closed containers that are near the source of the fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use. Read label before use.

Article No.: 34501001
Print date: 10.12.2018
Version: 2.1

Empire Dirt Blocker
Revision date: 11.06.2018
Issue date: 24.04.2018

EN
Page 4 / 8

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

propane-2-ol

INDEX No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0

WEL, TWA: 999 mg/m³; 400 ppm

WEL, STEL: 1250 mg/m³; 500 ppm

butane

INDEX No. 601-004-00-0 / EC No. 203-448-7 / CAS No. 106-97-8

WEL, TWA: 1450 mg/m³; 600 ppm

WEL, STEL: 1810 mg/m³; 750 ppm

Remark: (Carc, only applies if Butane contains more than 0.1% of buta-1,3-diene)

n-butyl acetate

INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

MEL/OES, TWA: 724 mg/m³; 150 ppm

MEL/OES, STEL: 966 mg/m³; 200 ppm

Additional information

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Recommended Respiratory protection: Respiratory protective device with half mask filter material type A. The standards EN 136, 140 and 405 of the European Commission for Standardization (CEN) make recommendations to respirators, the standards EN 149 and EN 143 provide recommendations to respiratory filters.

Hand protection

For prolonged or repeated handling the following glove material must be used: FKM (fluoro rubber) / NBR (Nitrile rubber)

Thickness of the glove material \geq 0,7 mm

Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.,

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

*

Appearance:

Physical state:

Liquid

Colour:

clear

Odour:

like organic solvents

Article No.: 34501001
Print date: 10.12.2018
Version: 2.1

Empire Dirt Blocker
Revision date: 11.06.2018
Issue date: 24.04.2018

EN
Page 5 / 8

Odour threshold:	not determined
pH at20 °C::	not applicable
Melting point/freezing point:	not determined
Initial boiling point and boiling range:	not determined
Flash point:	-60 °C Method: DIN 51755 part 1
Evaporation rate:	not determined
Flammability (solid, gas):	
Burning time (s):	not determined
Upper/lower flammability or explosive limits:	
Lower explosion limit:	1,69 Vol-%
Upper explosion limit:	12 Vol-% Source: propane-2-ol
Vapour pressure at20 °C::	982,242 mbar
Vapour density:	not determined
Relative density:	
Density at20 °C::	0,73 g/cm³ Method: DIN EN ISO 15212-1
Solubility(ies):	
Water solubility (g/L) at20 °C::	partially soluble
Partition coefficient: n-octanol/water:	see section 12
Auto-ignition temperature:	365 °C Source: butane
Decomposition temperature:	not determined
Viscosity at20 °C::	< 10 mPa-s Method: DIN 53019
Explosive properties:	not applicable
Oxidising properties:	not applicable

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP]
No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

n-butyl acetate

oral, LD50, Rat: 10760 mg/kg

Method: OECD 423

dermal, LD50, Rabbit: > 14112 mg/kg

Article No.: 34501001 Empire Dirt Blocker
Print date: 10.12.2018 Revision date: 11.06.2018
Version: 2.1 Issue date: 24.04.2018

EN
Page 6 / 8

Method: OECD 402
inhalative (Gases), LC50, Rat: 23,4 ppmV (4 h)
Method: OECD 403

propane-2-ol
oral, LD50, Rat: 5280 mg/kg
Method: OECD 401
dermal, LD50, Rabbit: 13900 mg/kg
Method: OECD 402
inhalative (vapours), LC50, Rat: > 25 mg/l (6 h)
Method: OECD 403

skin corrosion/irritation; Serious eye damage/eye irritation

n-butyl acetate
Skin, Rabbit
Method: OECD 404
eyes
Method: OECD 405

propane-2-ol
eyes
Method: OECD 405
Liquid splashes can lead to irritations of the eyes.

Respiratory or skin sensitisation

n-butyl acetate
Skin, Guinea pig: ; evaluation not sensitising.
Method: OECD 406

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

Toxicological data are not available.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Remark

There is no information available on the preparation itself .

SECTION 12: Ecological information

overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. Toxicity

n-butyl acetate
Fish toxicity, LC50, Pimephales promelas (fathead minnow): 18 mg/l (96 h)
Method: OECD 203
Daphnia toxicity, EC50, Daphnia magna (Big water flea): 44 mg/l (48 h)
Algae toxicity, ErC50, Desmodesmus subspicatus: 647,7 mg/l (72 h)

propane-2-ol
Algae toxicity, ErC50: > 1000 mg/l
, EC50, Scenedesmus subspicatus: > 100 mg/l (72 h)

Article No.: 34501001
Print date: 10.12.2018
Version: 2.1

Empire Dirt Blocker
Revision date: 11.06.2018
Issue date: 24.04.2018

EN
Page 7 / 8

Bacteria toxicity: > 100 mg/l

Long-term Ecotoxicity

n-butyl acetate

Algae toxicity, NOEC, *Desmodesmus subspicatus*: 200 mg/l

Inhibition of growth rate.

Bacterial toxicity:, IC50:, *Tetrahymena*: 356 mg/l (40 h)

12.2. Persistence and degradability

n-butyl acetate

Biodegradation:, aerobic: 83 % (28 D); evaluation Readily biodegradable (according to OECD criteria).

Method: OECD 301D/ EEC 92/69/V, C.4-E

propane-2-ol

: 95 % (5 D); evaluation Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

n-butyl acetate

Partition coefficient: n-octanol/water: 2,3

Method: OECD 117

Surface tension:, 1 g/l; 20°C: 61,3 mN/m

Method: OECD 115

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

160504 Gases in pressure containers (including halons) containing hazardous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

UN 1950

14.2. UN proper shipping name

Land transport (ADR/RID):

Aerosols, flammable

Sea transport (IMDG):

AEROSOLS

Air transport (ICAO-TI / IATA-DGR):

Aerosols, flammable

14.3. Transport hazard class(es)

2.1

14.4. Packing group

not applicable

14.5. Environmental hazards

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Article No.: 34501001
Print date: 10.12.2018
Version: 2.1

Empire Dirt Blocker
Revision date: 11.06.2018
Issue date: 24.04.2018

EN
Page 8 / 8

Further information

Land transport (ADR/RID)

tunnel restriction code D

Sea transport (IMDG)

EmS-No. F-D, S-U

Air transport (ICAO-TI / IATA-DGR)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

VOC Switzerland:

weight fraction in %: 99,30

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

15.2. Chemical Safety Assessment

For the following substances of this preparation a chemical safety assessment has been carried out:

EC No.	Chemical name	REACH No.
CAS No. 200-661-7 67-63-0	propane-2-ol	01-2119457558-25
204-658-1 123-86-4	n-butyl acetate	01-2119485493-29

SECTION 16: Other information

Full text of classification in section 3:

Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
compressed gas / H280	Gases under pressure	Contains gas under pressure; may explode if heated.
Flam. Gas 1 / H220	flammable gases	Extremely flammable gas.
Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version